

FACT SHEET

Pressure Equalizing Unit



Pressure equalizing unit
made by ElringKlinger

The housing of an energy storage represents a large, closed air volume. To avoid damage caused by pressure differences (environment, temperature changes, transport), pressure compensation with the environment is required.

Pressure equalizing units from ElringKlinger with integrated safety function compensate pressure differences. Due to the integrated emergency degassing function, the pressure equalizing unit releases a large cross section in the event of the outgassing of a battery cell, thus enabling a controlled degassing from the storage housing. The use of a specially developed PTFE membrane ensures a high air flow rate.



ELRINGKLINGER – YOUR PARTNER E-MOBILITY SOLUTIONS WITH BATTERY TECHNOLOGY

Cell Expertise – Module and System Design – Installation Space Optimization – Simulation and Testing – Certification – Prototyping – Process Engineering – Industrialization – Integrated Solutions and Components – Recycling

Technology

DIMENSIONS (L x W x H)	85 x 65 x 29 mm
AIR COMPENSATION CAPABILITY (AT 10 MBAR DIFFERENCE PRESSURE)	≥ 2 l/min
DEGASSING CROSS-SECTION	~ 620 mm ²
PRESSURE THRESHOLD FOR EMERGENCY DEGASSING	< 250 – 350 mbar
IP RATING (ACC. ISO 20653)	IPX9K IP6X IPX7 IPXXB (in normal operation)
FLAMMABILITY	UL94-V0
OPERATING TEMPERATURE	-40 to 100 °C
EMC	EMC protection can be provided upon request

Mounting

The assembly takes place via a screw flange or bayonett flange. In case of a screw flange the threads in the storage wall can be screwed via threaded holes or e.g. via inserts. The tightness requirements of the flange must be ensured by the customer. The PEU will be delivered with a preassembled non loosable gasket and 100% end-of-lineleakage tested.

YOUR CONTACT

ElringKlinger AG
Phone +49 7123 724-0
E-mail info@elringklinger.com

ElringKlinger AG | Max-Eyth-Straße 2 | 72581 Dettingen/Erms | Germany
www.elringklinger.com

The information provided in this document is the result of technological analyses and may be subject to changes depending on the design of the system. We reserve the right to make technical changes and improvements. The information is not binding and does not represent warranted characteristics. We do not recognize any claims for compensation based on this information. We accept no liability for printing errors.



08/23